

Package ‘tetraclasse’

October 14, 2022

Type Package

Title Satisfaction Analysis using Tetraclasse Model and Llosa Matrix

Version 0.1.21

Author vincent guyader

Maintainer vincent guyader <vincent@thinkr.fr>

Description

The satisfaction Analysis using the tetraclasse model from Sylvie Llosa. Llosa (1997) <<http://www.jstor.org/stable/40592578>>.

License GPL-3

Encoding UTF-8

LazyData true

Imports ggplot2, reshape2, tidyr, FactoMineR, magrittr, tibble, ggrepel, dplyr

RoxygenNote 6.0.1

NeedsCompilation no

Repository CRAN

Date/Publication 2017-07-15 21:14:59 UTC

R topics documented:

gen_avis	2
gen_llosa	2
Llosa	3
prepare_base	3
tetraclasse	4

Index	5
--------------	----------

gen_avis	<i>gen_avis</i>
----------	-----------------

Description

generate some random data

Usage

```
gen_avis(N)
```

Arguments

N	number of person
---	------------------

Examples

```
base <- gen_avis(50)
```

gen_llosa	<i>gen_llosa</i>
-----------	------------------

Description

plot the Llosa matrix

Usage

```
gen_llosa(dataset, borne = FALSE, annotate = TRUE,  
  annotatetext = c("Secondaire", " Plus", "Basique", "Clef"))
```

Arguments

dataset	the dataset to use
borne	booleen do you want xlim and ylim
annotate	booleen do you want annotation
annotatetext	annotation text

Examples

```
library(tetraclasse)  
gen_avis(100) %>%  
  prepare_base() %>%  
  gen_llosa()
```

Llosa	<i>gen_llosa</i>
-------	------------------

Description

hack CA objet

Usage

Llosa(BID)

Arguments

BID CA objet to hack

prepare_base	<i>prepare_base</i>
--------------	---------------------

Description

reshape the base

Usage

prepare_base(base, satis_col = "satis")

Arguments

base the base to reshape
satis_col satisfaction column name

Examples

```
base <- gen_avis(150)
prepare_base(base)
```

tetraclasse

tetraclasse

Description

Satisfaction Analysis - Tetraclasse Model And Llosa Matrix.

Examples

```
library(tetraclasse)

# generate an example dataset with 150 respondent
base <- gen_avis(150)

#prepare the dataset
base <- prepare_base(base)

# construct the Llosa matrix
gen_llosa(base)
if(require("dplyr")){
gen_avis(500) %>%
  sample_n(50,replace = TRUE)%>%
  prepare_base() %>%
  gen_llosa()

gen_avis(500) %>%
  prepare_base() %>%
  gen_llosa()
}
```

Index

[gen_avis](#), 2

[gen_llosa](#), 2

[Llosa](#), 3

[prepare_base](#), 3

[tetraclasse](#), 4

[tetraclasse-package \(tetraclasse\)](#), 4