

The titlesec and titletoc Packages*

Javier Bezos[†]

2007-08-12

Contents

- 1. Introduction 1**
- 2. Quick Reference 2**
 - 2.1. Format, 2.—2.2. Spacing, 2.—2.3. Tools, 2.
- 3. Advanced Interface 3**
 - 3.1. Format, 3.—3.2. Spacing, 4.—3.3. Spacing related tools, 5.—3.4. Rules, 6.—3.5. Page styles, 7.—3.6. Breaks, 7.—3.7. Other Package Options, 8.—3.8. Extended Settings, 8.—3.9. Creating new levels and changing the class, 9.
- 4. Additional Notes 10**
 - 4.1. Fixed Width Labels, 10.—4.2. Starred Versions, 10.—4.3. Variants, 11.—4.4. Putting a Dot after the Section Title, 12.
- 5. Page Styles 12**
 - 5.1. Defining Page Styles, 12.—5.2. Additional Settings, 14.—5.3. Running heads with floats, 14.—5.4. Marks, 15.—5.5. A couple of examples, 15.
- 6. Final comments 16**
- 7. Contents: The titletoc package 16**
 - 7.1. A ten-minute guide to titletoc, 17.—7.2. And more, 19.—7.3. Partial TOC's, 20.—7.4. Partial lists, 21.—7.5. Examples, 21.—7.6. Inserting a figure in the contents, 22.—7.7. Marking entries with asterisks, 22.
- 8. The titlesec philosophy 22**
- 9. Appendix 22**
 - 9.1. A full example, 26.—9.2. Standard Classes, 26.—9.3. Chapter Example, 27.

1. Introduction

This package is essentially a replacement—partial or total—for the \LaTeX macros related with sections—namely titles, headers and contents. The goal is to provide new features unavailable in current \LaTeX ; if you just want a more friendly interface than that of standard \LaTeX but without changing the way \LaTeX works you may consider using fancyhdr, by Piet van Oostrum, sectsty, by Rowland McDonnell, and tocloft, by Peter Wilson, which you can make pretty things with.

Some of the new features provided are:

- Different classes and “shapes” of titles, with tools for very fancy formats. You can define different formats for left and right pages, or numbered and unnumbered titles, measure the width of the title, add a new section level, use graphics, and many more. The Appendix shows a good deal of examples, so jump forward right now!
- Headers and footers defined with no `\dots.mark` intermediates, and perhaps containing top, first and bot marks at the same time. Top marks correctly synchronized with titles, and without

*The titlesec package is currently at version 2.8. © 1998–2007 Javier Bezos. The titletoc package is currently at version 1.6. © 1999–2007 Javier Bezos. All Rights Reserved.

[†]For bug reports, comments and suggestions go to <http://www.tex-tipografia.com/contact.html>. English is not my strong point, so contact me when you find mistakes in the manual. Other packages by the same author: gloss (with José Luis Díaz), enumitem, accents, tensind, esindex, dotlessi.

incompatibilities with the float mechanism. Decorative elements easily added, including picture environments.

- Pretty free form contents, with the possibility of grouping entries of different levels in a paragraph or changing the format of entries in the middle of a document.

Titlesec works with the standard classes and with many others, including the AMS ones, and it runs smoothly with `hyperref`.¹

As usual, load the package in the standard way with `\usepackage`. Then, redefine the sectioning commands with the simple, predefined settings (see section “Quick Reference”) or with the provided commands if you want more elaborate formats (see section “Advanced Interface.”) In the latter case, you only need to redefine the commands you’ll use. Both methods are available at the same time, but because `\part` is usually implemented in a non-standard way, it remains untouched by the simple settings and should be changed with the help of the “Advanced Interface.”

2. Quick Reference

The easiest way to change the format is by means of a set of package options and a couple of commands. If you feel happy with the functionality provided by this set of tools, you needn’t go further in this manual. Just read this section and ignore the subsequent ones.

2.1. Format

There are three option groups controlling font, size and align. You need not set all of these groups, since a default is provided for each one; however, you must use at least an option from them if you want this “easy setup.”

```
rm sf tt md bf up it sl sc
```

Select the corresponding family/series/shape. Default is `bf`.

```
big medium small tiny
```

Set the size of titles. Default is `big`, which gives the size of standard classes. With `tiny`, sections (except chapters) are typed in the text size. `medium` and `small` are intermediate layouts.

```
raggedleft center raggedright
```

Control the alignment.

2.2. Spacing

```
compact
```

This option is independent from those above and reduces the spacing above and below the titles.

2.3. Tools

```
\titlelabel{<label-format>}
```

Changes the label format in sections, subsections, etc. A `\thetitle` command is provided which is respectively `\thesection`, `\thesubsection`, etc. The default value in standard classes is

```
\titlelabel{\thetitle\quad}
```

and you may add a dot after the counter simply with

```
\titlelabel{\thetitle.\quad}
```

¹However, be aware that the AMS classes reimplement the original internal commands. These changes will be lost here. The compatibility with `hyperref` has been tested with `dvips`, `dvipdfm` and `pdftex` but it’s an unsupported feature. Please, check that your version of `hyperref` is compatible with `titlesec`.

That was done in this document.

```
\titleformat*{<command>}{<format>}
```

This command allows to change the *<format>* of a sectioning command, as for example:

```
\titleformat*{\section}{\itshape}
```

3. Advanced Interface

Two commands are provided to change the title format. The first one is used for the “internal” format, i. e., shape, font, label. . . , the second one defines the “external” format, i. e., spacing before and after, indentation, etc. This scheme is intended to easy definitions, since in most of cases you will want to modify either spacing or format.² That redefines existing sectioning commands, but does not create *new* ones. New sectioning levels can be added with `\titleclass`, as described below, and then their format can be set with the commands described here.

3.1. Format

A set of shapes is provided, which controls the basic distribution of elements in a title. The available shapes are:

hang is the default value, with a hanging label. (Like the standard `\section`.)

block typesets the whole title in a block (a paragraph) without additional formatting. Useful in centered titles³ and special formatting (including graphic tools such as `picture`, `pspicture`, etc.)

display puts the label in a separate paragraph. (Like the standard `\chapter`.)

runin A run-in title. (Like the standard `\paragraph`.)

leftmargin puts the title at the left margin. Titles at the very end of a page will be moved to the next one and will not stick out in the bottom margin, which means that large titles can lead to underfull pages.⁴ In this case you may increase the stretchability of the page elements, use `\raggedbottom` or use the package option `nobottomtitles` described below. Since the mechanism used is independent from that of the margin pars, they can overlap. A deprecated synonymous is `margin`.

rightmargin is like `leftmargin` but at the right margin.

drop wraps the text around the title, provided that the first paragraph is longer than the title (if not, they overlap). The comments in `leftmargin` also applies here.

wrap is quite similar to `drop`. The only difference is that while the space reserved in `drop` for the title is fixed, in `wrap` is automatically readjusted to the longest line. The limitations explained below related to `calwidth` also applies here.

frame similar to `display`, but the title will be framed.

Note, however, that some shapes don’t make sense in chapters and parts.

```
\titleformat{<command>}[<shape>]{<format>}{<label>}{<sep>}{<before>}[<after>]
```

Here

²Information is “extracted” from the class sectioning commands, except for chapter and part. Standard definitions with `\@startsection` are presumed—if sections have been defined without that macro, arbitrary values for the format and the spacing are provided, which you may change later. (Sadly, there is no way to catch the chapter or part formats, and one similar to that of standard classes will be used.)

³The label will be slightly displaced to the left if the title is two or more lines long and the `hang` shape is used, except with explicit `\.`

⁴However, floats following the title a couple of lines after will interfere with the page breaking used here and sometimes the title may stick out.

- $\langle command \rangle$ is the sectioning command to be redefined, i. e., `\part`, `\chapter`, `\section`, `\subsection`, `\subsubsection`, `\paragraph` or `\subparagraph`.
- The paragraph shape is set by $\langle shape \rangle$, whose possible values are those described above.
- $\langle format \rangle$ is the format to be applied to the whole title—label and text. This part can contain vertical material (and horizontal with some shapes) which is typeset just after the space above the title.
- The label is defined in $\langle label \rangle$. You may left it empty if there is no section label at that level, but note that by doing so the number is not suppressed in the table of contents and running heads.
- $\langle sep \rangle$ is the horizontal separation between label and title body and must be a length (it cannot be left empty). This space is vertical in `display` shape; in `frame` it is the distance from text to frame. Both $\langle label \rangle$ and $\langle sep \rangle$ are ignored in starred versions of sectioning commands. If you are using `picture` and the like, set this parameter to 0 pt.
- $\langle before \rangle$ is code preceding the title body. The very last command can take an argument, which is the title text.⁵ However, with the package option `explicit` the title must be given explicitly with #1 (see below).
- $\langle after \rangle$ is code following the title body. The typeset material is in vertical mode with `hang`, `block` and `display`; in horizontal mode with `runin` and `leftmargin` (2.7) with the latter, at the beginning of the paragraph). Otherwise is ignored.

```
\chaptertitlename
```

It defaults to `\chaptername` except in appendices where it is `\appendixname`. Use it instead of `\chaptername` when defining a chapter.

3.2. Spacing

```
\titlespacing*{<command>}{<left>}{<beforesep>}{<aftersep>}[<right>]
```

The starred version kills the indentation of the paragraph following the title, except in `drop`, `wrap` and `runin` where this possibility does not make sense.

- $\langle left \rangle$ increases the left margin, except in the `...margin`, and `drop` shape, where this parameter sets the title width, in `wrap`, the maximum width, and in `runin`, the indentation just before the title. With negative value the title overhangs.⁶
- $\langle beforesep \rangle$ is the vertical space before the title.
- $\langle aftersep \rangle$ is the separation between title and text—vertical with `hang`, `block`, and `display`, and horizontal with `runin`, `drop`, `wrap` and `...margin`. By making the value negative, you may define an effective space of less than `\parskip`.⁷
- The `hang`, `block` and `display` shapes have the possibility of increasing the $\langle right \rangle$ margin with this optional argument.

If you dislike typing the full skip values, including the `plus` and `minus` parameters, an abbreviation $*n$ is provided. In the $\langle beforesep \rangle$ argument this is equivalent to `n ex` with some stretchability and a minute shrinkability. In the $\langle aftersep \rangle$ some stretchability (smaller) and no shrinkability.⁸ Thus, you can write

⁵Remember that font size can be changed safely between paragraphs only, and that changes in the text should be made local with a group; otherwise the leading can be wrong—too large or too small.

⁶This parameter is not equal to `<indent>` of `\startsection`, which doesn't work correctly. With a negative value in the latter and if `<indent>` is larger than the label width, the first line of the title will start in the outer margin, as expected, but the subsequent lines will not; worse, those lines will be shortened at the right margin.

⁷See Goossens, Mittelbach and Samarin: *The L^AT_EX Companion*, Reading, Addison Wesley, 1993, p. 25.

⁸They stand for `n times lex plus .3ex minus .06ex` and `lex plus .1ex`, respectively.

```
\titlespacing{\section}{0pt}{*4}{*1.5}
```

The lengths `\beforetitleunit` and `\aftertitleunit` are used as units in the `*` settings and you can change them if you don't like the predefined values (or for slight changes in the makeup, for example).

Notes. `\titlespacing` does not work with neither `\chapter` nor `\part` unless you change its title format as well by means of `\titleformat`, the simple settings, or `\titleclass`. Arguments in `\titlespacing` must be dimensions; `\stretch` includes a command and hence raises an error.

3.3. Spacing related tools

These commands are provided as tools for `\titleformat` and `\titlespacing`.

```
\filright \filcenter \filleft \fillast \filinner \filouter
```

Variants of the `\ragged...` commands, with slight differences. In particular, the `\ragged...` commands kills the left and right spaces set by `\titlespacing`. `\fillast` justifies the paragraph, except the last line which is centered.⁹ These commands work in the frame label, too.

`\filinner` and `\filouter` are `\filleft` or `\filright` depending on the page. Because of the asynchronous \TeX page breaking, these commands can be used in `\chapter` only. If you want a general tool to set different formats depending on the page, see “Extended settings” below.

```
\wordsep
```

The inter-word space of the current font.

```
indentafter noindentafter (Package options)
```

By-pass the settings for all of sectioning commands.¹⁰

```
rigidchapters rubberchapters (Package options)
```

With `rigidchapters` the space for chapter titles is always the same, and `\aftersep` in `\titlespacing` does not mean the space from the bottom of the text title to the text body as described above, but from the *top* of the text title, i. e., `\beforesep` + `\aftersep` now is a fixed distance from the top of the page body to the main text. The default is `rubberchapters` where `\aftersep` is the separation between title and text as usual. Actually, the name is misleading because it applies not only to the default chapter, but to any title of top class. (More on classes below.)

```
bottomtitles nobottomtitles nobottomtitles* (Package options)
```

If `nobottomtitles` is set, titles close to the bottom margin will be moved to the next page and the margin will be ragged. The minimal space required in the bottom margin not to move the title is set (approximately) by

```
\renewcommand{\bottomtitlespace}{\langle length \rangle}
```

whose default value is `.2\textheight`. A simple ragged bottom on the page before is obtained with a value of 0 pt. `bottomtitles` is the default, which simply sets `\bottomtitlespace` to a negative value.

The `nobottomtitles*` option provides more accurate computations but titles of margin, wrap or drop shapes could be badly placed. Usually, you should use the starred version.

```
aftersep largestsep (Package options)
```

By default, when there are two consecutive titles the `\aftersep` space from the first one is used between them. Sometimes that is not the desired behaviour, especially when the `\beforesep` space is

⁹Admittedly, a weird name, but it's short.

¹⁰Formerly `indentfirst` and `nonindentfirst`, now deprecated.

much larger than the *⟨aftersep⟩* one (otherwise the default seems preferable). With `largestsep` the largest of them is used. Default is `aftersep`.

```
\\ \\*
pageatnewline (Package option)
```

2.6 The package option `pageatnewline` is for backward compatibility. In 2.6, `\\` does not allow a page break and therefore is equivalent to `*`. Since I presume none wants a page break inside a title, this has been made the default. If for some extrange reason you want to allow page breaks inside the titles, use the package option.

3.4. Rules

The package includes some tools for helping in adding rules and other stuff below or above the title. Since the margins in titles may be modified, these macros take into account the local settings to place rules properly. They also take into account the space used by marginal titles.

```
\titleline[⟨align⟩]{⟨horizontal material⟩}
\titlerule[⟨height⟩]
\titlerule*[⟨width⟩]{⟨text⟩}
```

The `\titleline` command allows inserting a line, which may contain text and other “horizontal” material. It’s intended mainly for rules and leaders but in fact is also useful for other purposes. The line has a fixed width and hence must be filled, i.e., `\titleline{CHAPTER}` produces an underfull box. Here the optional *⟨align⟩* (l, r or c) helps, so that you simply type, say, `\titleline[c]{CHAPTER}`.¹¹

Using `\titleline` in places where vertical material is not expected can lead to anomalous results. In other words, you can use it in the *⟨format⟩* (always) and *⟨after⟩* (hang, display and block) arguments; and in the display shape at the very beginning of the *⟨before⟩* and *⟨label⟩* argument as well. But try it out, because it’s very likely it works in other places.

The `\titlerule` command, which is enclosed automatically in `\titleline` if necessary, can be used to build rules and fillers. The unstarred version draws rules of height .4 pt, or *⟨height⟩* if present. For example:

```
\titlerule[.8pt]%
\vspace{1pt}%
\titlerule
```

draws two rules of different heights with a separation of 1 pt.

The starred version makes leaders with the *⟨text⟩* repeated in boxes of its natural width. The width of the boxes can be changed to *⟨width⟩*, but the first box remains with its natural width so that the *⟨text⟩* is aligned to the left and right edges of the space to be filled.

For instance, with

```
\titleformat{\section}[leftmargin]
{\titlerule*[1pc]{.}%
 \vspace{1ex}%
 \bfseries}
{... definition follows}
```

leaders spanning over both main text and title precede the section.

```
calcwidth (Package option)
```

The `wrap` shape has the capability of measuring the lines in the title to format the paragraph. This capability may be extended to other three shapes—namely `display`, `block` and `hang`—with this package option. The length of the longest line is returned in `\titlewidth`.

As far as T_EX is concerned, any box is considered typeset material. If the box has been enlarged with blank space, or if conversely a box with text has been smashed, the value of `\titlewidth` may be

¹¹The default is the `s` parameter of the `\makebox` command.

wrong (as far as humans is concerned). The `hang` shape, for instance, uses internally such a kind of boxes, but in this case this behaviour is desired when the title is flushed right; otherwise the `block` shape produces better results. In other words, using boxes whose natural width has been overridden may be wrong.¹² Further, some commands may confuse TeX and stop parsing the title. But if you stick to text, `\` and `\\[. . .]` (and it's very unlikely you might want something else), there will be no problems. Another important point is that the `<before>`, `<label>`, `<sep>`, and `<title>` parameters (but not `<after>`) are evaluated twice at local scope; if you increase a counter *globally*, you are increasing it twice. In most of cases, placing the conflicting assignment in the `<after>` parameter will be ok.¹³

We now describe a variant of `\titleline`.

```
\titleline*[{<align>}]{<horizontal material>}
```

The text will be enclosed first in a box of width `\titlewidth`; this box will be in turn enclosed in the main box with the specified alignment. There is no equivalent `\titlerule` and therefore you must enclose it explicitly in a `\titleline*` if you want the `\titlewidth` to be taken into account:

```
\titleline*[c]{\titlerule[.8pc]}
```

3.5. Page styles

2.8 You can assign a page style to levels of class `top` and `page`, as well as the default chapter with the following command:¹⁴

```
\assignpagestyle{<command>}{<pagestyle>}
```

For example, to suppress the page number in chapters write:

```
\assignpagestyle{\chapter}{empty}
```

3.6. Breaks

```
\sectionbreak      \subsectionbreak      \subsubsectionbreak
\paragraphbreak    \subparagraphbreak
```

By defining these command with `\newcommand` different page breaks could be applied to different levels. In those undefined, a penalty with the internal value provided by the class is used (typically `-300`). For instance,

```
\newcommand{\sectionbreak}{\clearpage}
```

makes sections begin a new page. In some layouts, the space above the title is preserved even if the section begins a new page; that's accomplished with:

```
\newcommand{\sectionbreak}{%
  \addpenalty{-300}%
  \vspace*{0pt}}
```

2.6 Until now, `\. . .break` was allowed only in the straight class, but now it's available in the `top` class, too. Suitable values would be `\cleardoublepage` (the default if `openright`) and `\clearpage` (the default if `openany`). Thus, you can override `openright` by defining `\chapterbreak` as `\clearpage`, provided its class has been changed to `top` (in this example, parts will continue with the `openright` setting).

¹²Which include justified lines, whose interword spacing has been enlarged.

¹³There are two further parameters, `\titlewidthfirst` and `\titlewidthlast`, which return the length of the first and last lines. There are not specific tools for using them, but you can assign their values to `\titlewidth` and then use `\titleline*`.

¹⁴Named in the short-lived version 2.7 as `\titlepagestyle`.

`\chaptertolists`

2.6 If defined, the usual white space written to lists (ie, List of Figures and List of Tables) is replaced by the code in this command. If you don't want the white space when a chapter begins, define it to empty. This command is not a general tool to control spacing in lists, and is available only in titles of top class, so it will not work with the default chapters except if you change their class (on the other hand, `\...tolists` can be used in any title whose class is top).

3.7. Other Package Options

`explicit` (Package option)

2.7 With it, the title is not implicit after *<before>* but must be given explicitly with #1 as in, for example:

```
\titleformat{\section}
{..}
{\thesection}{..}{#1.}
```

(Compare it with the example in section 4.4.)

`newparttoc oldparttoc` (Package options)

Standard parts write the toc entry number in a non standard way. You may change that with `newparttoc` so that `titletoc` or a similar package can manipulate the entry. (That works only if `\part` has been redefined.)

`cleareempty` (Package options)

Modifies the behaviour of `\cleardoublepage` so that the `empty` page style will be used in empty pages.

`toctitles` (Package option)

2.6 Changes the behaviour of the optional argument in sectioning titles so that it sets only the running heads and not the TOC entries, which will be based on the full title.

`newlinetospace` (Package option)

2.6 Replaces every occurrence of `\\` or `*` in titles by a space in running heads and TOC entries. This way, you don't have to repeat the title just to remove a formatting command.

3.8. Extended Settings

The first argument of both `\titleformat` and `\titlespacing` has an extended syntax which allows to set different formats depending on the context.¹⁵ This argument can be a list of key/value pairs in the form:

`<key>=<value>, <key>=<value>, <key>, <key>, ...`

Currently, only pages and unnumbered versions are taken care of, besides the sectioning command name. Thus, the available keys are:

- `name`. Allowed values are `\chapter`, `\section`, etc.
- `page`. Allowed values are `odd` or `even`.

¹⁵The `keyval` package is required for making use of it.

- `numberless`. A valueless key. It's not necessary unless you want to set different numbered (without this key) and unnumbered (with `numberless`) variants.

The basic form described above with the name of a sectioning command, say

```
\titleformat{\section} ...
```

is in fact an abbreviation for

```
\titleformat{name=\section} ...
```

Let's suppose that we'd like a layout with titles in the outer margin. We may set something like

```
\titleformat{name=\section,page=even}[leftmargin]
{\filleft\scshape}{\thesection}{.5em}{}
```

```
\titleformat{name=\section,page=odd}[rightmargin]
{\filright\scshape}{\thesection}{.5em}{}
```

Since the page information is written to the `aux` file, at least two runs are necessary to get the desired result.

The “number” version is usually fine when generating unnumbered variants since removing the label is the only change required in most cases, but if you need some special formatting, there is the `numberless` key which defines an alternative version for sections without numbers (namely those with level below `secnumdepth`, in the front and back matters and, of course, the starred version). For instance

```
\titleformat{name=\section}{...% The normal definition follows
\titleformat{name=\section,numberless}{...% The unnumbered
% definition follows
```

Neither $\langle label \rangle$ nor $\langle sep \rangle$ are ignored in `numberless` variants.

These keys are available to both `\titleformat` and `\titlespacing`. By using `page` in one (or both) of them, odd and even pages will be formatted differently. Actually, “even” and “odd” are well established L^AT_EX terms, but misleading. In one side printing the “odd” pages refer to “even” pages as well (cf. `\oddsidemargin`.)

If you intend to create different odd/even *and* different numbered/unnumbered versions, it's recommended defining the four variants.

If you remove the page specifier from a sectioning command you must remove the `.aux` file.

3.9. Creating new levels and changing the class

While the shapes and the like modify the behaviour of titles related to the surrounding text, title classes allow to change the generic behaviour of them. With the help of classes you may insert, say, a new subchapter level between `chapter` and `section`, or creating a scheme of your own. *Making a consistent scheme and defining all of related stuff like counters, macros, format, spacing and, if there is a TOC, TOC format is left to the responsibility of the user.* There are three classes: `page` is like the book `\part`, in a single page, `top` is like `\chapter`, which begins a page and places the title at the top, and `straight` is intended for titles in the middle of text.¹⁶

```
\titleclass{\name}{\class}
\titleclass{\name}{\class}[\sup-level]
```

If you don't use the optional argument, you just change the $\langle class \rangle$ of $\langle name \rangle$. For example:

```
\titleclass{\part}{straight}
```

makes `part` of `straight` class.

When the second form is used, the level number is the following of $\langle sup-level \rangle$. For example:

¹⁶There is an further class named `part` to emulate the article `\part`, but you should not use it at all. Use the `straight` class instead. Remember that some features rely in these classes and that `titlesec` does not change by default the definition of `\part` and `\chapter`.

```
\titleclass{\subchapter}{straight}[\chapter]
\newcounter{subchapter}
\renewcommand{\thesubchapter}{\Alph{subchapter}}
```

creates a level under chapter (some additional code is shown as well, but you must add to it the corresponding `\titleformat` and `\titlespacing` settings).¹⁷ If the chapter level is 0, then the subchapter one is 1; the levels below are increased by one (section is 2, subsection is 3, and so on).

There are two sectioning commands which perform some extra actions depending of its name and ignoring the class:

- `\chapter` logs the string defined in `\chaptertitlename` and the matter is taken into account.
- `\part` does not encapsulates the label in the toc entry, except if you use the `newparttoc` option.

`loadonly` (Package option)

Now, you want to create your sectioning commands from scratch. This package option ignores any previous definitions, if any, and hence removes the possibility of using the option described in “Quick Reference.” Then you use the `titlesec` tools, and define the corresponding counters and labels.

`\titleclass{<name>}[<top-num>]{<class>}`

Here, the `<name>` title is considered the top level, with `<top-num>` level number (typically 0 or -1). It should be used only when creating sectioning commands from scratch with the help of `loadonly`, and there must be exactly one (no more, no less) declaration of this kind. After it, the rest of levels are added as explained above.

4. Additional Notes

This part describes briefly some \LaTeX commands, useful when defining sectioning titles.

4.1. Fixed Width Labels

The `\makebox` command allows to use fixed width label, which makes the left margin of the actual title (not the label) to lie in the same place. For instance (only the relevant code is provided):

```
\titleformat{\section}
{..}
{\makebox[2em]{\thesection}}{..}{..}
```

See your \LaTeX manual for further reference on boxing commands.

4.2. Starred Versions

The use of sectioning commands in the starred version is strongly discouraged. Instead, you can use a set of markup oriented commands which are easy to define and modify, if necessary. Thus, you can test different layouts before choosing amongst them.

Firstly remember that if you say

```
\setcounter{secnumdepth}{0}
```

sections will be not numbered but they will be included in both toc and headers.

Now, let’s suppose that you want to include some sections with a special content; for example, a section (or more) with exercises. We will use an environment named `exercises` whose usage is:

```
\section{A section}
Text of a normal section.

\begin{exercises}
\section{Exercises A}
Some exercises
```

¹⁷Regarding counters, the `remreset` package can be useful.

```
\section{Exercises B}
Some exercises
\end{exercises}
```

The following definition suppresses numbers but neither toc lines nor headers.

```
\newenvironment{exercises}
  {\setcounter{secnumdepth}{0}}
  {\setcounter{secnumdepth}{2}}
```

The following one adds a toc line but headers will remain untouched:

```
\newenvironment{exercises}
  {\setcounter{secnumdepth}{0}%
   \renewcommand\sectionmark[1]{} }
  {\setcounter{secnumdepth}{2}}
```

The following one updates the headers but there will be no toc line:

```
\newenvironment{exercises}
  {\setcounter{secnumdepth}{0}%
   \addtocontents{toc}{\protect\setcounter{tocdepth}{0}\ignorespaces}}
  {\setcounter{secnumdepth}{2}%
   \addtocontents{toc}{\protect\setcounter{tocdepth}{2}\ignorespaces}}
```

(I find the latter a bit odd in this particular example; the first and second options are more sensible. The `\ignorespaces` is not very important, and you needn't it unless there is unwanted space in the toc.)

That works with standard classes, but if you are using `fancyhdr` or `titlesec` to define headers you need further refinement to kill the section number. In `titlesec` that's accomplished with `\ifthissection` (see below).

As you can see, there are no `\addcontentsline`, no `\markboth`, no `\section*`, just logical structure. Of course you may change it as you wish; for example if you decide that these sections should be typeset in small typeface, include `\small`, and if you realize that you don't like that, remove it.

While the standard \LaTeX commands are easier and more direct for simple cases, I think the proposed method above is far preferable in large documents.

4.3. Variants

Let's suppose we want to mark some sections as "advanced topics" with an asterisk after the label. The following code does the job:

```
\newcommand{\secmark}{}
\newenvironment{advanced}
  {\renewcommand{\secmark}{*}}
  {}
\titleformat{\section}
  {...}
  {\thissection\secmark\quad}{...}{...}
```

To mark the sections write

```
\begin{advanced}
\section{...}
...
\end{advanced}
```

That marks sections but not subsections. If you like being redundant and marking the subsection level as well, you must define it accordingly.

4.4. Putting a Dot after the Section Title

Today this styling is not used, but formerly it was fairly common. The basic technique was described above, but here is a reminder:

```
\newcommand{\periodafter}[1]{#1.}
\titleformat{\section}
{..}
{\thesection}{..}{..\periodafter}
```

If you had to combine that dot with some command (perhaps an underlining), you can say:

```
\newcommand{\periodafter}[2]{#1{#2.}}
\titleformat{\section}
{..}
{\thesection}{..}{..\periodafter{\ul}} % \ul from soul package
```

You might prefer the package option `explicit`.

5. Page Styles

As a part of this package a set of commands are provided for one-step headline and footline settings. Those page styles has been designed to work with sectioning related information; you shouldn't use to create headers with the first and last entry of a page in a dictionary, for example (you could, but it's more complicated than with `fancyhdr`).

It works with standard classes and many others; however, additional L^AT_EX layout adjustments could be necessary in some of them (for instance the AMS classes).¹⁸ For using them, set the following package option:¹⁹

```
pagestyles
```

Once that has been done, you can define your own page styles and then activate them.²⁰

5.1. Defining Page Styles

```
\newpagestyle{<name>}[<global-style>]{<commands>}
\renewpagestyle{<name>}[<global-style>]{<commands>}
```

Defines a new style or redefines an existing one, named `<name>`. For convenience, end of lines are ignored, and you needn't "hide" them with `%`.²¹

`<global-style>` is any command to be applied to both footlines and headlines. Fragile commands are allowed.

In `<commands>` you can use (these commands are local to a page style, i.e., defining them directly in the preamble will not work because the page style settings will override them):

```
\headrule          \footrule
\setheadrule{<length>} \setfootrule{<length>}
```

If you want a rule below the headline and above the footline. You may also set their width directly with the commands `\setheadrule` and `\setfootrule`. (For instance, `\setheadrule{.4pt}` which is, by the way, the default value.)

¹⁸Two columns layout requires the `fix2col` package by David Carlisle.

¹⁹The way page styles works have been reimplemented in full in release 2.3. However, in most of cases you won't notice it at all.

²⁰Page styles so defined cannot be used with `\thispagestyle` except if the surrounding page style has been defined with `titlesec`, too.

²¹Even if marks should be reserved to pass information to headers, some classes, like AMS ones, introduce additional code. When redefining the `plain` style of AMS classes, you must add the following line: `\global\topskip\normaltopskip`.

```
\makeheadrule \makefootrule
```

These commands are used by `titlesec` to typeset the rules. If there is no rule, both commands are empty (this value is the default). `\setheadrule{dim}` just stands for

```
\renewcommand{\makeheadrule}{\rule[-.3\baselineskip]{\linewidth}{d}}
```

unless if `dim` is 0 pt, which empties `\makeheadrule` (and similarly `\setfootrule`).

You can access the total head/foot width with `\linewidth` but the box enclosing the rule is in fact dimensionless. Hence, you must be concerned with the rule placement only. Its baseline is the same as that of the head/foot. That means that the material to be used as rule should be raised or lowered with `\raisebox`, the lifting argument in `\rule` or by using sensible coordinates in `picture`, for instance. That makes easy to place material above *and* below. For instance, the following code creates a headline with a black bold line above and a red rule below (the color package is required):

```
\renewcommand{\makeheadrule}{%
  \makebox[0pt][l]{\rule[.7\baselineskip]{\linewidth}{0.8pt}}%
  \color[named]{Red}%
  \rule[-.3\baselineskip]{\linewidth}{0.4pt}}
```

Of course, the material to be used as rule is not restricted to actual rules; pictures and leaders, for instance, are allowed, too.

```
\sethead[<even-left>][<even-center>][<even-right>]{<odd-left>}{<odd-center>}{<odd-right>}
\setfoot[<even-left>][<even-center>][<even-right>]{<odd-left>}{<odd-center>}{<odd-right>}
```

Set the corresponding part in heads and foots. The optional arguments are all or none. If no optional arguments are given the odd-page settings applies to both even and odd pages. A couple of starred variant (`\setfoot*`, `\sethead*`) reverses the order of the settings for even pages (obviously, if you use them, the optional arguments are not allowed). In the arguments of `\sethead/\setfoot` and because of its one-step mechanism, we must distinguish between two groups of commands. The first one are those saved when the marks are sent, with information related to sections, and includes:

- `\thechapter`, `\thesection`...
- `\chaptertitle`, `\sectiontitle`... which print the chapter, section... title.
- `\ifthechapter{<true>}{<false>}`, `\ifthesection{<true>}{<false>}`... which expands to `<true>` except if the corresponding title lacks of label or there is no title yet after the superior level (for example, between `\chapter` and a subsequent `\section`).
- Any other command or value “registered” as “mark.” (See below.)

The second group are those expanded in every page, and includes:

- `\thepage`.
- Any other command not included in the previous items.

```
\setmarks{<primary>}{<secondary>}
```

Sets which `\...title` commands are to be defined, and when the marks are updated. For example `\setmarks{chapter}{section}` means that:

- `\chaptertitle` and `\sectiontitle` are the allowed titles in heads,
- `\sectiontitle` is reset in `\chapter`,
- `\ifthechapter` and `\ifthesection` are valid tests, and

- Marks are updated in `\chapter` and `\section`.

By default it is `\setmarks{chapter}{section}` but `\setmarks{section}{subsection}` in article class. `\setmarks` may be used outside `\(re)newpagestyle` to set the default to be used in newly defined and redefined page styles. Use it before `\pagestyle`.

Note that `\markboth` is a command to set the `myheadings` marks and here does not make sense. In fact, using it can lead to unpredictable results. Anyway, using directly the marking commands is discouraged (see sec. 4.2) but if you need them, you may use them as in:

```
\chapter*{My Chapter}
\chaptermark{My Chapter}
```

5.2. Additional Settings

```
\widenhead[⟨even-left⟩][⟨even-right⟩][⟨odd-left⟩][⟨odd-right⟩]
\widenhead*{⟨even-right⟩/⟨odd-left⟩/}[⟨even-left⟩/⟨odd-right⟩]
```

Makes the head/footer lines wider. The extra width is asymmetrically added and hence the two [four] arguments. Like `\sethead`, the starred version reverses the setting for even pages—for example, `\widenhead*{0pt}{6pc}` is the same as `\widenhead[6pc][0pt]{0pt}{6pc}`.

5.3. Running heads with floats

```
psfloats (Package option.)
```

This package option activates the commands described in this section.²²

2.6 The commands below now have a new argument to allow extra stuff in running heads/foots.

This change is backward compatible—just preserve the old name `floatps`, which is deprecated, if you want the old behaviour.

```
\setfloathead*{.}{.}{.}{⟨extra⟩}[⟨which-floats⟩]
\setfloathead[.][.][.]{.}{.}{.}{⟨extra⟩}[⟨which-floats⟩]
(Similarly \setfloatfoot.)
```

The arguments with a dot are similar to those of `\sethead`. The final argument says that head is used when there is a float of the specified types (default is `tp` in headers, and `bp` in footers). For example:

```
\newpagestyle{main}{%
  \sethead ... your definition
  \setfoot ... your definition
  \headrule
  \footrule
  \setfloathead{}{}{}{\setheadrule{0pt}}[p]
  \setfloatfoot{}{}{}{\setfootrule{0pt}}[p]}
```

removes the header/footer on float pages, including the rules.

```
\nextfloathead*{.}{.}{.}{⟨extra⟩}[⟨which-floats⟩]
\nextfloathead[.][.][.]{.}{.}{.}{⟨extra⟩}[⟨which-floats⟩]
(Similarly \nextfloatfoot.)
```

You may force a header (respectively footer) when a certain float is the first top (respectively last bottom) one with those commands, where the arguments with a dot are similar to those of `\sethead`, just before the corresponding float. Those commands are used by themselves, without putting them inside `\(re)newpagestyle`.

²²It redefines some internal L^AT_EX commands and there could be incompatibilities with other packages modifying the same commands. That's the very reason these commands are loaded only optionally.

5.4. Marks

```
outermarks innermarks topmarks botmarks (Package options)
```

`innermarks` is the default in \LaTeX , with bottom marks in even pages and first marks in odd pages. More convenient is `outermarks`, with top marks in even pages and bottom marks in odd pages; it's the more usual system in technical works and it's described in *The TeXbook*, p. 259. Both of them are intended for two side printing; `topmarks/botmarks` are intended for one side printing with top/bot marks in every page (they can be used in two side printing as well).²³

```
\bottitlemarks \toptitlemarks \firsttitlemarks \nexttoptitlemark
\outertitlemarks \innertitlemarks
```

One of the cooler features added to page styles is the possibility of selecting which marks are used in subsequent macros. These commands set from which mark the values of `\thesection`, `\sectiontitle`, etc. will be taken. You can use freely in your headers;²⁴ just for fun, the following header shows the section label from three of these marks:

```
\newpagestyle{funny}{
  \sethead{Top is \toptitlemarks\thesection}
          {First is \firsttitlemarks\thesection}
          {Bot is \bottitlemarks\thesection}}
```

`\outertitlemarks` is the default value when the `outermarks` package option is set, `\toptitlemarks` when `topmarks` is set, and so on. `\innertitlemarks` is the default value in \LaTeX and in this package if none of those option is used. A further set of marks is provided with `\nexttoptitlemarks` which provides a bottom mark with the values of the top mark of the next page (straight class only); by picking some value from it and comparing with the corresponding value of the `\bottitlemarks` you may know if a section continues in the next page. Of course, these commands will not be used very often.

```
\newtitlemark{<macro-name>}
\newtitlemark*{<variable-name>}
```

Add a macro or a variable to the list of “marks” to be saved. The macro must be parameterless, and the variable should be in TeX form (which is the same in lengths but not in counters—the latter take the form `\c@<counter>`).

5.5. A couple of examples

Because of the way marks are handled, special constructions like this are allowed:

```
\newpagestyle{main}[\small\sffamily]{
  \sethead [\textbf{\thepage}]
          [\textsl{\chaptertitle}]
          [[\toptitlemarks\thesection--\bottitlemarks\thesection]
          {\toptitlemarks\thesection--\bottitlemarks\thesection}]
          {\textsl{\sectiontitle}]
          {\textbf{\thepage}}}
```

As you can see, the range of sections in a page `\thesection` is printed in both left and right heads. Of course, this example should be fine tuned to collapse the ranges if there is a single section in a page, but it gives a hint of how to get stunning headers.

In this document, the following styles are used:

²³`outermarks` does not work well in conjunction with explicit `\<section>mark` commands. The top marks mechanism fails just after explicit page breaks.

²⁴Not exactly: top marks must not be used in the page where a chapter begins, except by overriding the default definition and making it of `top` class.

```

\widenhead{2.1pc}{0pc}
\renewpagestyle{plain}[\small\sffamily\slshape]{
  \footrule
  \setfoot{}{\thepage}{}}
\newpagestyle{mysp}[\small\sffamily\slshape]{
  \headrule
  \sethead{Titlesec}{\sectiontitle}{\thepage}}

```

The following definitions provide page styles similar to those of Lamport's \LaTeX book (with the `calc` package):

```

\widenhead*{0pt}{\marginparsep + \marginparwidth} % symmetrically
\renewpagestyle{plain}{}
\newpagestyle{latex}[\bfseries]{
  \headrule
  \sethead[\thepage][\chaptertitle]
    {\thesection\ sectiontitle}{\thepage}}
\pagestyle{latex}

```

6. Final comments

- Only a `\footnote` command is allowed in titles, but it will work. However, the footnote mark is not removed from toc entries or running headings; for that use

```
\usepackage[stable]{footmisc}
```

- The page styles have been reimplemented in full in version 2.3. Most of previous definition will work with the current code, even if many things have changed. In particular, headers using just `\the...` and `\...title` commands, besides `\usepage` and formatting commands still work. Now, `pagestyles` should be loaded explicitly with the `pagestyles` option, but if it is not given and the three basic commands are used, the page styles macros are loaded with a warning. The new code overcomes the limitations of previous releases, fixes some bugs (the incompatibility between top marks and floats, for example), and adds new features.

7. Contents: The `titletoc` package

This package is a companion to the `titlesec` package and it handles toc entries. However, it's an independent package and you can use it alone. The philosophy is similar to that of `titlesec`—instead of hooking the commands as defined by standard \LaTeX and classes, there are new commands which you can format the toc entries with in a generic way. That means that you have to learn just two new basic command and a couple of tools, no more, and that you have access to new features. Paragraph format and fonts are set with commands like `\`, `\makebox`, `\large`, `\itshape`, and so on, and entries are not shaped in any fashion because they are pretty free form.

The behaviour of entries defined with `titletoc` are different at some points to that created with the standard commands. In particular:


- Pages are never broken between entries if the first one is of an higher level than the second one as, for instance, between a section and a subsection. If both of them are of the same level, the break is allowed, and if the first is lower than the second, it's considered a good place for a page break.
- The symbols in the leaders are not centered but flushed right. That is usually more convenient.

I would like to note that no attempt to handle tocs can be complete because the standard \LaTeX commands write directly some formatting commands which cannot be removed. This is particularly important in lists of figures and tables, and in the `\part` command.²⁵


²⁵But some of these issues are fixed by `titlesec`.

7.1. A ten-minute guide to titletoc


Toc entries are treated as rectangular areas where the text and probably a filler will be written. Let's draw such an area (of course, the lines themselves are not printed):



The space between the left page margin and the left edge of the area will be named $\langle left \rangle$; similarly we have $\langle right \rangle$. You are allowed to modify the beginning of the first line and the ending of the last line. For example by “taking up” both places with $\backslash hspace*{2pc}$ the area becomes:



And by “clearing” space in both places with $\backslash hspace*{-2pc}$ the area becomes:



If you have seen tocs, the latter should be familiar to you– the label at the very beginning, the page at the very end:

```
3.2 This is an example showing that toc
    entries fits in that scheme . . . . 4
```

All you need is to put these elements in the right way. If you have reserved the space with $\backslash hspace*{-2pc}$, simply put a box 2 pc width containing the section label or page so that this space will be retrieved; this layout is used so often that two commands are provided which does that for you:

- $\backslash contentslabel\{\langle length \rangle\}$ creates the space at the beginning and prints the section number.
- $\backslash contentspage$ creates a space at the end of length $\langle right \rangle$ and prints the page number aligned at the right.

Now, we are about to show the three basic commands:

```
\dottedcontents{\section}[\langle left \rangle]{\langle above \rangle}
{\langle label width \rangle}{\langle leader width \rangle}
```

Here:

- $\langle section \rangle$ is the section name without backslash: part, chapter, section, etc. figure and table are allowed, too. (The backslash is omitted because we are dealing with the concept and not the $\backslash part$, $\backslash section$, etc. macros themselves. Furthermore, figure and table are environments.)
- $\langle above \rangle$ is code for the global formatting of the entry. Vertical material is allowed. At this point the value of $\backslash thecontentslabel$ (see below) is known which enables you to take decisions depending on its value (with the help of the ifthen package). You may use the titlesec $\backslash filleleft$, $\backslash filright$, $\backslash filcenter$ and $\backslash fillast$ commands.

- `<left>` even if bracketed is currently mandatory and it sets the left margin from the left page margin.
- `<label width>` is the width of the space created for the label, as described above.
- `<leader width>` is the width of the box containing the char to be used as filler, as described below.

The definitions for section and subsection entries in the book class are roughly equivalent to:

```
\contentsmargin{2.55em}
\dottedcontents{section}[1.5em]{}{2.3em}{1pc}
\dottedcontents{subsection}[3.8em]{}{3.2em}{1pc}
```

```
\titlecontents{<section>}[<left>]{<above>}
  {<before with label>}{<before without label>}
  {<filler and page>}[<after>]
```

Here `<section>`, `<left>` and `<above>` like above, and

- `<before with label>` is in horizontal mode and it will be used just before the entry title. As in `\titleformat`, the last command can take an argument with the title.
- `<before without label>` is like the above if there is, well, no label.
- `<filler and page>` is self explanatory. Fillers are created with the `\titlerule` command which is shared by that package and `titlesec`. However, when used in this context its behaviour changes a little to fit the needs of toc leaders.²⁶ You might prefer a `\hspace` instead.
- And finally `<after>` is code following the entry for, say, vertical space.

When defining entries, use `\addvspace` if you want to add vertical space, and `*` instead of `\\` for line breaks.

This command can be used in the middle of a document to change the format of toc/lot/lof entries at any point. The new format is written to the toc file and hence two runs are necessary to see the changes.

```
\contentsmargin{<right>}
```

The value set is used in all of sections. If you are wondering why, the answer is quite simple: in most of cases the `<right>` margin will be constant. However, you are allowed to change it locally in the `<before>` arguments. Note as well that the default space in standard classes does not leave room to display boldfaced page number above 100 and therefore you might want to set a larger margin with this command.

The book class formats section entries similarly (but not equally) to:

```
\titlecontents{section}
  [1.5em]
  {}
  {\contentslabel{2.3em}}
  {\hspace*{-2.3em}}
  {\titlerule*[1pc]{.}\contentspage}
```

Compare this definition with that given above and you will understand how `\dottedcontents` is defined.

Although standard classes use font dependent units (mainly em), it's recommended using absolute ones (pc, pt, etc.)

²⁶For T_EXnicians, the default `\xleaders` becomes `\leaders`.

7.2. And more

Strict typographical rules state that full text lines shouldn't surpass the last dot of the leaders; ideally they should be aligned. Surprisingly enough, TeX lacks of a tool for doing that automatically—when you fill a box with leading dots, they can be centered in the box with the `\cleaders` primitive, “justified” with `\xleaders` or aligned with the outermost enclosing box with `\leaders`, but there is no way to align them with the “current” margin.

So, the only way to get a fine layout is by hand. To do, you can use the an optional argument in the `\contentsmargin` command whose syntax in full is the following:

```
\contentsmargin[⟨correction⟩]{⟨right⟩}
```

The `⟨correction⟩` length is added to the `⟨right⟩` one in all of lines except the last one, where the leaders are placed. For instance, if the text lines are 6 pt longer than the last dot, you should rewrite the `\contentsmargin` command to add a `⟨correction⟩` of 6 pt.²⁷ Unlike the standard L^AT_EX tools, the `\titlerule*` command has been designed so the `⟨correction⟩` will have the minimum value possible.

```
\thecontentslabel \thecontentspage
```

Contains the text with the label and the page with no additional formatting, except written by the class.

```
\contentslabel[⟨format⟩]{⟨space⟩}
\contentspage[⟨format⟩]
```

As described above, but with different `⟨format⟩`s. The defaults are just `\thecontentslabel` and `\thecontentspage`, respectively.

```
\contentspush{⟨text⟩}
```

Prints the `⟨text⟩` and increases `⟨left⟩` by the width of `⟨text⟩`. is similar to the hang shape of titlesec.

```
\titlecontents*{⟨section⟩}[⟨left⟩]{⟨above⟩}
    {⟨before with label⟩}{⟨before without label⟩}
    {⟨filler and page⟩}[⟨separator⟩]
    or ...{⟨filler and page⟩}[⟨separator⟩][⟨end⟩]
    or ...{⟨filler and page⟩}[⟨begin⟩][⟨separator⟩][⟨end⟩]
```

This starred version groups the entries in a single paragraph. The `⟨separator⟩` argument is the separator between entries, and there is a further optional argument with an ending punctuation. For example, this document sets:

```
\titlecontents*{subsection}[1.5em]
  {\small}
  {\thecontentslabel. }
  {}
  {, \thecontentspage}
  [---][.]
```

whose result is showed in the contents at the very beginning of this document. Note the paragraph format must be written in the `⟨above⟩` argument.

Let's explain how the optional arguments works. First note the number of them determines their meaning—since there should be a separator between entries this one is always present; on the other hand, `⟨begin⟩` is rarely used and hence it has the lowest “preference.” The simplest case is when the titles are of the same level; in this case the `⟨sep⟩` and the `⟨end⟩` parameters (which default to empty) are

²⁷Usefully, many dvi previewers allow to get the coordinates of the pointed location.

inserted between consecutive entries and at the end of the block, respectively. $\langle before \rangle$ is executed just once at the very beginning of the block and its declarations are local to the whole set of entries.

Let's now suppose we want to group entries of two levels; in this case a nesting principle applies. To fix ideas, we will use section and subsection. When a subsection entry begins after a section one, $\langle before \rangle$ is executed and $\langle begin \rangle$ of subsection is inserted, which should contain text format only. Then subsections are added inserting separators as explained above. When a section arrives, the ending punctuation of subsection and the separator of section is added (except if the block is finished by a subsection, where the ending of section is added instead). We said "after a section" because a subsection never begins a block.²⁸ The subsection entries are nested inside the section ones, and declarations are again local.

An example will illustrate that.

```
\titlecontents*{section}[0pt]
  {\small\itshape}{}{}
  {}[ \textbullet\ ]{.}

\titlecontents*{subsection}[0pt]
  {\upshape}{}{}
  {, \thecontentspage}[ (][. ]{)}
```

produces something similar to:

The first section • The second one • The third one (A subsection in it, 1. Another, 2) • *A fourth section* (A subsection in it, 1. Another, 2).

```
\contentsuse{<name>}{<ext>}
```

Makes titletoc aware of the existence of a contents file with $\langle ext \rangle$ extension. Mainly, it makes sure that the command `\contentsfinish` is added at the end of the corresponding contents (and which must be added at the end of tocs made by hand). The package performs

```
\contentsuse{figure}{lof}
\contentsuse{table}{lot}
```

```
leftlabels rightlabels (Package options)
```

These package options set how the labels are aligned in `\contentslabel`. Default is `rightlabels`. With `leftlabels` the default $\langle format \rangle$ for `\contentslabel` becomes `\thecontentstlabel\enspace`.

```
dotinlabels (Package option)
```

With this package option, a dot is added after the label in `\contentslabel`.

7.3. Partial TOC's

```
\startcontents[<kind>]
```

At the point where this command is used, a partial toc begins. The $\langle kind \rangle$ argument allows different sets of tocs and it defaults to `default`. These sets may be intermingled, but usually will be nested. For example, you may want two kinds of partial tocs: by part and by chapter (besides the full toc, of course). When a part begins, write `\startcontents[parts]`, and when a chapter `\startcontents[chapters]`. This way a new toc is started at each part and chapter.²⁹

```
\stopcontents[<kind>]
\resumecontents[<kind>]
```

Stops the partial toc of $\langle kind \rangle$ kind, which may be resumed. Since partial contents are stopped by `\startcontents` if necessary, you won't use those macros very often.

²⁸In rare cases that could be necessary, yet.

²⁹All partial tocs are stored in a single file with extension `.ptc`.

```
\printcontents[<kind>]{<prefix>}{<top>}{<init-code>}
```

Print the current partial toc of *<kind>* kind. The format of the main toc entries are used, except if there is a *<prefix>*. In such a case, the format of *<prefix><level>* is used, provided it is defined. For example, if *prefix* is *l* and the format of *lsection* is defined, then this definition will be used; otherwise, the format is that of *section*. The *<top>* parameter sets the top level of the tocs—for a part toc it would be 0 (chapter), for a chapter toc 1 (section), and so on. Finally, *<init-code>* is local code for the current toc; it may be used to change the *tocdepth* value or *\contentsmargin*, for instance.

A simple usage might look like (provided you are using *titlesec* as well):

```
\titleformat{\chapter}[display]
{...}{...}{...} % Your definitions come here
[\vspace*{4pc}]%
\startcontents
\printcontents{1}{1}{\setcounter{tocdepth}{2}}

\titlecontents*{lsection}[0pt]
{\small\itshape}{}{}
{}[ \textbullet\ ]{.}
```

The included entries are those in the level from 1 to 2 inclusive.

7.4. Partial lists 2.6

You may want to create partial LOFs and LOTs. The syntax is similar to that of partial TOCs and what was said for them can be applied here. The commands are:

```
\startlist[<kind>]{<list>}
\stoplist[<kind>]{<list>}
\resumelist[<kind>]{<list>}
\printlist[<kind>]{<list>}{<prefix>}{<init-code>}
```

Here *<list>* is either *lof* or *lot*. Note as well *\printlist* does not have the *<top>* argument, because figures and tables have not levels. Currently (version 2.8), only these two floats are supported, but in a future release support for more kinds of floats will be added. Unfortunately, many classes write some formatting commands to these lists (more precisely, *\addvspaces* in chapters); I'm still not sure how to remove these commands without removing as well others which can be wanted, but for the time being a quick trick to remove these spaces is to redefine *\addvspace* in the *<init-code>* with *\renewcommand\addvspace[1]{}*.

7.5. Examples

```
\titlecontents{chapter}
[0pt]
{\addvspace{1pc}%
\itshape}%
{\contentsmargin{0pt}%
\bfseries
\makebox[0pt][r]{\huge\thecontentslabel\enspace}%
\large}
{\contentsmargin{0pt}%
\large}
{\quad\thepage}
[\addvspace{.5pc}]
```

The chapter number is out at the edge of the page margin, in a font larger than the font of the title. If the chapter lacks of number (because, say, it is the preface or the bibliography) it is not boldfaced. The page number follows the title without fillers, but after an em-space.

```
\titlecontents{chapter}
[3pc]
{\addvspace{1.5pc}%
```

```

\filcenter}
{CHAPTER \thecontentslabel\*[.2pc]%
\huge}
{\huge}
{} % That is, without page number
[\addvspace{.5pc}]

```

The chapter title is centered with the chapter label on top of it. There is no page number.

7.6. Inserting a figure in the contents

The `\addtocontents` command is still available and you may use it to perform special operation, like inserting a figure just before or after of an entry. Sadly, fragile arguments are not allowed and writing complex code could be a mess. The trick is to define a command to perform the required operations which in turn is written with `\protect`.

Let's suppose that we want to insert a figure before an entry.

```

\newcommand{\figureintoc}[1]{
\begin{figure}
\includegraphics{#1}%
\end{figure}}

```

makes the dirty work.

In the place where a figure is inserted write:

```

\addtocontents{\protect\figureintoc{myfig}}

```

7.7. Marking entries with asterisks

Let's now resume a problem explained in relation with `titlesec`: marking sections with asterisks to denote an "advanced topic" unless that the star should be printed in the toc as well. Here is the code:

```

\newcommand{\secmark}{}
\newcommand{\marktoc}[1]{\renewcommand{\secmark}{#1}}
\newenvironment{advanced}
{\renewcommand{\secmark}{*}%
\addtocontents{toc}{\protect\marktoc{*}}}
{\addtocontents{toc}{\protect\marktoc{}}}
\titleformat{\section}
{..}
{\thesection\secmark}{..}{..}
\titlecontents{section}[..]{..}
{\contentslabel[\thecontentslabel\secmark]{1.5pc}}{..}{..}

```

8. The titlesec philosophy

Once you have read the documentation it should be clear that this is not a package for the casual user who likes the standard layout and wants to make simple changes. This is a tool for the serious typographer that has a clear idea of what layout wants and don't have the skill to get it. No attempt is made to improve your taste in section formatting.

9. Appendix

The following examples will be illustrative. In this part, the `\parskip` is 0 pt.

■

10 This is an example of the section command defined below and, what's more, this is an example of the section command defined below

```

\titleformat{\section}[block]
{\normalfont\bfseries\filcenter}{\fbox{\itshape\thesection}}{1em}{}

```

■

SECTION 11

A framed title

```
\titleformat{\section}[frame]
{\normalfont}
{\filright
\footnotesize
\enspace SECTION \thesection\enspace}
{8pt}
{\Large\bfseries\filcenter}
```



12. A Ruled Title

```
\titleformat{\section}
{\titlerule
\vspace{.8ex}%
\normalfont\itshape}
{\thesection.}{.5em}{}
```



13

Another Ruled Title

```
\titleformat{\section}[block]
{\normalfont\sffamily}
{\thesection}{.5em}{\titlerule\[\.8ex]\bfseries}
```



.....

14 The length of the “rule” above is that of the longest line in
this title increased by two picas

.....

15 This one is shorter

```
\titleformat{\section}[block]
{\filcenter\large
\addtolength{\titlewidth}{2pc}%
\titleline*[c]{\titlerule* [.6pc]{\tiny\textbullet}}%
\advvspace{6pt}%
\normalfont\sffamily}
{\thesection}{1em}{}
```

```
\titlespacing{\section}
{5pc}{*2}{*2}[5pc]
```



SECTION 16

This is an example of the section command defined below and, what’s more, this is an example of the section command defined below. Let us repeat it. This is an example of the section command defined below and, what’s more, this is an example of the section command defined below

```
\titleformat{\section}[display]
{\normalfont\fillast}
{\scshape section \oldstylenums{\thesection}}
```

```
{1ex minus .1ex}
{\small}
\titlespacing{\section}
{3pc}{*3}{*2}[3pc]
```

■

THIS PART IS THE TITLE ITSELF and this part is the section body...

```
\titleformat{\section}[runin]
{\normalfont\scshape}
{}{0pt}{}
\titlespacing{\section}
{\parindent}{*2}{\wordsep}
```

■

17. A Simple Example of the “wrap” Section Shape Which is followed by some text to show the result. Which is followed by some text to show the result. Which is followed by some text to show the result. Which is followed by some text to show the result. Which is followed by some text to show the result. Which is followed by some text to show the result.

18. And another Note how the text wraps the title and the space reserved to it is readjusted automatically. And that is followed by some text to show the result. Which is followed by some text to show the result.

```
\titleformat{\section}[wrap]
{\normalfont\fontseries{b}\selectfont\filright}
{\thesection.}{.5em}{}
\titlespacing{\section}
{12pc}{1.5ex plus .1ex minus .2ex}{1pc}
```

■

§ 19. Old-fashioned runin title.—Of course, you would prefer just a dot after the title. In this case the optional argument should be [.] and the space after a sensible value (1em, for example).

```
\titleformat{\section}[runin]
{\normalfont\bfseries}
{\S\ \thesection.}{.5em}{[.---]}
\titlespacing{\section}
{\parindent}{1.5ex plus .1ex minus .2ex}{0pt}
```

■

.....

Example of margin section

Which is followed by some text to show the result. But don't stop reading, because the following example illustrates how to take advantage of other packages. The last command in the last argument can take an argument, which is the title with no additional command inside it. We just give the code, but you may try it by yourself. Thus, with the soul package you may say

```
\newcommand{\secformat}[1]{\MakeLowercase{\so{#1}}}
% \so spaces out letters
\titleformat{\section}[block]
{\normalfont\scshape\filcenter}
{\thesection}
{1em}
{\secformat}
```

The margin title above was defined:


```

\titleformat{\section}[leftmargin]
  {\normalfont
   \titlerule*{.6em}{\bfseries.}%
   \vspace{6pt}%
   \sffamily\bfseries\filleft}
  {\thesection}{.5em}{}
\titlespacing{\section}
  {4pc}{1.5ex plus .1ex minus .2ex}{1pc}

```

■

The following examples are intended for chapters. However, this document lacks of `\chapter` and are showed using `\sections` with slight changes.

CHAPTER 20

The Title

```

\titleformat{\chapter}[display]
  {\normalfont\Large\filcenter\sffamily}
  {\titlerule[1pt]%
   \vspace{1pt}%
   \titlerule
   \vspace{1pc}%
   \LARGE\MakeUppercase{\chaptertitlename} \thechapter}
  {1pc}
  {\titlerule
   \vspace{1pc}%
   \Huge}

```

■

CHAPTER XXI

The Title

```

\renewcommand{\thechapter}{\Roman{chapter}}
\titleformat{\chapter}[display]
  {\bfseries\Large}
  {\filleft\MakeUppercase{\chaptertitlename} \Huge\thechapter}
  {4ex}
  {\titlerule
   \vspace{2ex}%
   \filright}
  [\vspace{2ex}%
   \titlerule]

```

9.1. A full example

Now an example of a complete title scheme follows.

```

\documentclass[twoside]{report}
\usepackage[sf,sl,outermarks]{titlesec}

% \chapter, \subsection...: no additional code

\titleformat{\section}
  {\LARGE\sffamily\slshape}
  {\thesection}{1em}{}
\titlespacing{\section}
  {-6pc}{3.5ex plus .1ex minus .2ex}{1.5ex minus .1ex}

\titleformat{\paragraph}[leftmargin]
  {\sffamily\slshape\filright}
  {}{}{}
\titlespacing{\paragraph}
  {5pc}{1.5ex minus .1ex}{1pc}

% 5+1=6, ie, the negative left margin in section

\widenhead{6pc}{0pc}

\renewpagestyle{plain}{}

\newpagestyle{special}[\small\sffamily]{
  \headrule
  \sethead[\usepage][\textsl{\chaptertitle}][
    ]{\textsl{\chaptertitle}}{\usepage}}

\newpagestyle{main}[\small\sffamily]{
  \headrule
  \sethead[\usepage][\textsl{\thechapter. \chaptertitle}][
    ]{\textsl{\thesection. \sectiontitle}}{\usepage}}

\pagestyle{special}

\begin{document}

---TOC

\pagestyle{main}

---Body

\pagestyle{special}

---Index
\end{document}

```

9.2. Standard Classes

Now follows, for your records, how sectioning commands of standard classes could be defined.

```

\titleformat{\chapter}[display]
  {\normalfont\huge\bfseries}{\chaptertitlename\ \thechapter}{20pt}{\Huge}
\titleformat{\section}
  {\normalfont\Large\bfseries}{\thesection}{1em}{}
\titleformat{\subsection}
  {\normalfont\large\bfseries}{\thesubsection}{1em}{}
\titleformat{\subsubsection}

```

```

{\normalfont\normalsize\bfseries}{\thesubsubsection}{1em}{}
\titleformat{\paragraph}[runin]
{\normalfont\normalsize\bfseries}{\theparagraph}{1em}{}
\titleformat{\subparagraph}[runin]
{\normalfont\normalsize\bfseries}{\thesubparagraph}{1em}{}

\titlespacing*{\chapter}      {0pt}{50pt}{40pt}
\titlespacing*{\section}     {0pt}{3.5ex plus 1ex minus .2ex}{2.3ex plus .2ex}
\titlespacing*{\subsection}  {0pt}{3.25ex plus 1ex minus .2ex}{1.5ex plus .2ex}
\titlespacing*{\subsubsection}{0pt}{3.25ex plus 1ex minus .2ex}{1.5ex plus .2ex}
\titlespacing*{\paragraph}   {0pt}{3.25ex plus 1ex minus .2ex}{1em}
\titlespacing*{\subparagraph}{\parindent}{3.25ex plus 1ex minus .2ex}{1em}

```

9.3. Chapter Example

A final example shows how to take advantage of the `picture` environment for fancy sectioning formats. Even with the simple tools provided by standard \LaTeX you may create impressive titles but you may devise more elaborated ones with, for instance, `pspicture` (PSTricks package) or by including graphics created with the help of external programs.

```

\usepackage[dvips]{color}
\usepackage[rigidchapters,explicit]{titlesec}

\DeclareFixedFont{\chapterfont}{T1}{phv}{bx}{n}{11cm}

\titlespacing{\chapter}{0pt}{0pt}{210pt}
% Most of titles have some depth. The total space is
% a bit larger than the picture box.

\titleformat{\chapter}[block]
{\begin{picture}(330,200)}
{\put(450,80){%
\makebox(0,0)[rb]{%
\chapterfont\textcolor[named]{SkyBlue}{\thechapter}}}}
\put(0,230){%
\makebox(0,0)[lb]{%
\Huge\sffamily\underline{Chapter \thechapter}}}}
{0pt}
{\put(0,190){\parbox[t]{300pt}{%
\Huge\sffamily\filright#1}}}
[\end{picture}]

```

(The exact values to be used depend on the text area, class, `\unitlength`, paper size, etc.)